Engineered to perform

- · Welded, multi-chamber frame and sash
- · Interlocking sash with heavy-duty weatherstripping
- · 3 1/4" frame depth
- · Available frame styles: finless, mounting fin
- Wood extension jambs available for 4 %16" and 6 %16" wall depths

Min and max sizing

WIDTH		HEIGHT	
MIN	MAX	MIN	MAX
	2-LITE (ox or xo)	
23 1/2"	84"	14"	63"
23 1/2"	72"	14"	72"
	3-LITE	(XOX)	N .
46 1/2"	117 1/2"	15"	72"

Available in 1/8" increments.

Energy efficient glass

Optional tempered glass adds additional strength and obscure or rain glass allows light in while protecting privacy.

GLAZING TYPE	U-VALUE	SHGC	этс
Argon and Low-E glass	0.27	0.26	29
Argon and Low-Eglass with grids	0.27	0.23	29
Argon and HP Low-E glass	0.28	0.21	29
Argon and HP Low-E glass with grids	0.28	0.19	29
Argon and Low-E triple-pane glass	0.22	0.22	28
Argon and Low-E triple-pane glass with grids	0.23	0.20	28
Krypton and Low-E triple-pane glass*	0.18	0.22	28
Krypton and Low-E triple-pane glass with grids*	0.18	0.19	28

Note: all values based on standard 3/4" dual-pane or 7/8" triple-pane insulated glass unit unless noted otherwise

* Meets U-Factor and Solar Heat Cain Coefficient (SHCC) requirements to be recognized as ENERGY STAR Most Efficient

Create a customized look

Enhance your home's spaces with a variety finish options and grid configurations.

FINISH OPTIONS

TERIOR	INTERIOR	
White EXTRUSION	White EXTRUSION	
Almond Paint / Extrusion	Almond EXTRUSION	
Clay PAINT / EXTRUSION	Clay EXTRUSION:	
Cocoa	Hillside Oak Laminate	
Cream	Natural Oak Laminate	
Forest Green	Colonial Cherry	
Bronze PAINT		
Black Matte		

GRID TYPES



- † Clay interior available on products manufactured in Texas only; may only be combined with clay extruded exterior; not available with triple-pane glass
- Black exterior not available with woodgrain interiors











